

AMP15 AMP30

Amplifiers for Permanent Installation

*MADE IN USA



FEATURES

- 4 Ohm, 8 Ohm, 25V, and 70V output
- 3 mixing channels
- Tone Control
- MIC/TEL Page Input, balanced, with screw terminal connectors
- AUX program Input via RCA jacks
- Automatic Mute
- Adjustable Music-On-Hold
- Five Year Warranty

DESCRIPTION

The AMP15 & AMP30 offers 15 Watt and 30 Watt output respectively and are ideal for a wide variety of paging background music and music on hold applications. Both units feature a selectable, balanced MIC/TEL input via screw terminals, an electronically combined program input via RCA jacks and an auxiliary input along with a separate 1 Watt music on hold output channel.

Each unit features a tone control and an adjustable MOH output. With cold rolled steel chassis, the AMP15 and AMP30 offer years of trouble-free operation backed up by 5-year Warranty. Typical installations are convenience stores, fast food establishments, offices, and any other application where a combination of paging, background music and music on hold is called for.

APPLICATION

Models were designed with the accurate reproduction of voice announce, paging and background music in mind. They are ideally suited for applications such as restaurants, country clubs, halls, sports venues, factories, retail stores, warehouse, churches, transportation facilities and other public areas.

The program section receives stereo input from cassette recorders, CD players, TVs or broadcast transmission and reproduces it in monaural.



SPECIFICATIONS

POWER OUTPUT (RMS)

AMP15: 15watts
AMP30: 30watts

DISTORTION:

Less Than 1% at Rated Output

FREQUENCY RESPONSE

Program: 50-20 KHz
Telephone: 50-20 KHz
Microphone: 50-20 KHz

HUM AND NOISE (BELOW -44 DBM)

Program Input: -75 dB
Mic/Tel Input: -55 dB

GAIN

Program Input: 55 dB
Mic/Tel Input: 107 dB

MUTING

Microphones: Mic/Tel VOX Priority over channel 1 & 2, with mute defeat button

SENSITIVITY CONTROL:

Mic/Tel and Channel 1 & 2 on front panel

INPUT AND OUTPUT CONNECTION:

Mic/Tel screw terminal,
Channel 1 & 2 RCA only

INPUT AND OUTPUT CONNECTION:

Screw Terminals

MOUNTS:

Four Cushioned Pads (Provided) or
RB-1 Optional Rack-Mount Accessory

POWER SUPPLY:

110 volts

ADJUSTMENT KNOBS:

Plastic -Black Trimmed in White

HOUSING MATERIAL:

Cold Rolled Steel

FINISH:

Black

DIMENSIONS, INCH (MM):

9.5"W x 3.5"H x 7.5"D

NET WEIGHT LBS (KGS)

AMP15: 8 lbs.
AMP30: 9 lbs.

7